

Rotary Evaporator STRIKE 380



Evaporate laboratory solvents in maximum safety

Health and safety at the workplace are undoubtedly one of the foundations of international social policies. Several official documents regulate the objective of progressive improvement at workplace well-being. This law focuses on accident and disease prevention by limiting the use of dangerous substances (when possible) or by minimizing contact at the workplace and with workers. A common aim of the numerous publications is to define good practice, make it known and then develop it to the point where working conditions favour greater worker safety and health. To instill a culture of prevention and to change attitudes, it is necessary to improve understanding of risk for the people directly involved, through education, by making them aware as well as and helping them anticipate new risks. It is also essential to integrate health and workplace safety into company management and in other activities that lead to a systematic approach to workplace well-being, thus adapting to all the changes that normally take place. The risk prevention attitude must be consolidated by demonstrating that effective workplace safety and health policies are a strategic factor in market competition and that, in contrast, absence of these policies brings added costs.

Innovations

The following are the technical innovations applied to the construction of the Strike 380.

Rotary Evaporator making it a fast, efficient, safe and maintenance-free instrument.

Design

Compact and modern. All controls are placed on the central column to guarantee user-friendly and handy use.



Control panel

The touch screen is wide and easy to read. The microprocessor is multi-programmable and GLP compliant.




Powered glassware

Compact and modern. All controls are placed on the central column to guarantee user-friendly and handy use.



Integrated vacuum controller

The optional vacuum controller is managed by the touch screen display that comes as standard



Sealing system

The exclusive sealing system allows a perfect vacuum-tight anti-corrosion seal without gaskets or other materials that can be damaged by solvent contact. This sealing system is a standard feature in all strike models and can be used with all types of glassware.



Rotary evaporator innovations

The following are the technical innovations applied to the construction of the STRIKE 300 Rotary Evaporator making it a fast, working, efficient, safe and maintenance free instrument.



Flask assembly

System used to assemble the evaporation flask. The evaporation flask is screwed onto the steam passing pipe to ensure easy assembly and dismantling operations as well as a perfect seal. (You may also use conventional unthreaded cone flasks and spring-clamps to mount the flasks).



Safety shield

The shield is standard for all models. It can be removed by the operator and fitted beside the instrument.



Specifications

Technical data	STRIKE 300
Models	Models available with slanting glassware, vertical glassware (steam sinking and steam rising type)
Glassware	Standard or plastic-coated glassware
Rotation speed	20 to 280 rpm (150W induction motor)
Screen	3.5" monochromatic LCD touch screen
sealing	Maintenance-free PTFE and carbon graphite seals
Connection	Rodavis evaporation flask connection system
Bath temperature	185°C (2 possible settings: water and oil)
Bath heater	1400W
Bath capacity	5 liters
Bath material	PTFE coated
Bath movement distance	90mm
Draining	Removable bath for emptying
Stroke displacement	13cm, adjusted, and can be stop at any position
Head angle adjustable	0~15°
Cooling surface	1500cm ²
Evaporating flasks	1000ml (optional 50 to 2000ml)
Collecting flasks	1000ml (optional 250 to 2000ml)
Weight	26,5 Kg (vertical version), 26 Kg (slanting version)
Overall dimensions	690x700x430mm (vertical version, H x D x L) 690x790x430mm (slanting version, H x D x L)
Voltage	230 V AC, 50Hz
Options	Steam temperature probe, vacuum controller
protective shield	Glassware lifting made possible with or without protective shield
Other features	Powered glassware lifting equipment with safety release (in case of power failure) Quick Start/Stop control and parameter selector

Control panel and microprocessor

- 3.5" LCD graphic display touch screen (320 x 240 pixel)
- START/STOP control and quick basic parameter selection
- Real-time display of all basic operating parameters (bath temperature, rotation speed), vacuum level and fume temperature (if optional probe and vacuum controller are present)
- Real-time display of working method
- Method saving and retrieving (up to 10 methods)
- Timer
- Possibility to operate according to fume temperature (if optional probe is present)
- Possibility to create manual and automatic ramps according to time, by differentiating all working parameters (if vacuum controller is present)

- Possibility to download working method to PC through USB port and retrieve it at any time
- USB updatable multi-language software.

Models of STRIKE 380



Strike 380 M1 / M4
Slanting glassware



Strike 380 M2 / M5
Vertical glassware (Steam sinking type)



Strike 380 M3 / M6
Vertical glassware (Steam rising type)

Configurations in standard glassware

Order Number	Model	Type	Voltage	Version
SQED060113	Rot.Evap.STRIKE 380 M1	Slanting glassware	220V	O
SQED060112	Rot.Evap.STRIKE 380 M2	Vertical glassware (Steam sinking type)	220V	V
SQED060111	Rot.Evap.STRIKE 380 M3	Vertical glassware(Steam rising type)	220V	U

Configurations in plastic coated safety glassware

Order Number	Model	Type	Voltage	Version
SQED060419	Rot.Evap.STRIKE 380 M4	Slanting glassware	220V	O/P
SQED060418	Rot.Evap.STRIKE 380 M5	Vertical glassware (Steam sinking type)	220V	V/P
SQED060417	Rot.Evap.STRIKE 380 M6	Vertical glassware(Steam rising type)	220V	U/P
SQED060420	Rot.Evap.STRIKE 380 M7	Dry ice condensation type	220V	C

NOTE: Other glassware versions are available upon specific request

WIGGENS GmbH

Gässlesweg 22-24, 75334 Straubenhardt, Germany
Tel.: 0049 7248 4529088

WIGGENS China

Room 426, Hall A, Office Building M8, No.1 Jiuxianqiao East Road,
Chaoyang District, Beijing 100015, China
Tel: +86 400-809-2068
Fax: +86 400-809-2068-112
Email: info@wiggins.com service@wiggins.com
Website: www.wiggins.com